

Energy Saving RO Membrane Elements

Applications

- Groundwater, tap water treatment etc.
- Supply system for dairy and beverage production, municipal drinking water, agricultural water, 2nd pass RO feed water etc.
- Feed TDS below 1000mg/L.

Benefits

- High Permeability
- Low Operating Pressure
- Cost-effective

8040 Elements



Specifications

Model	Active Area ft ² (m ²)	Feed Spacer Thickness(mil)	Permeate Flow Rate GPD(m ³ /d)	Stabilized Salt Rejection (%)
XLP-8040	440(40.9)	28	11000(41.6)	99.20

Standard Test Condition

Solution	Temperature (°C)	pH	Operating Pressure psi(MPa)	Recovery (%)
500mg/L NaCl	25	7.5-8.0	100(0.69)	15

Individual flow rate may vary ±15%

4040 Elements



Specifications

Model	Active Area ft ² (m ²)	Feed Spacer Thickness(mil)	Permeate Flow Rate GPD(m ³ /d)	Stabilized Salt Rejection (%)
XLP-4040	90(8.4)	28	2600(9.8)	99.20
XLP-4040HF	100(9.3)	28	3000(11.4)	99.00

Standard Test Condition

Solution	Temperature (°C)	pH	Operating Pressure psi(MPa)	Recovery (%)
500mg/L NaCl	25	7.5-8.0	100(0.69)	15

Individual flow rate may vary ±15%

Element Dimensions and Operating Limits

Model	Length		Diameter		Permeate Tube inner Diameter		Permeate Tube Extension Length	
	inch	mm	inch	mm	inch	mm	inch	mm
8040	40	1016	7.9	201	1.12	28.5	/	/
4040	40	1016	3.9	99	0.75	19.1	1.04	26.5

Maximum Operating Pressure	600psi(4.14MPa)
Maximum Operating Temperature	45°C
Maximum Feed Silt Density Index (SDI ₁₅)	5.0
Free Chlorine Tolerance	0.1mg/L
pH Range,Continuous Operation	3-10
pH Range,Short-Term Cleaning	1-13
Maximum Element Pressure Drop	15psi(0.1MPa)

All pictures for reference only.Please contact KeenSen for further advise.