






 <p>Powered by <b>Sterilight</b></p>	 <p>Powered by <b>Sterilight</b></p>	 <p>Powered by <b>Sterilight</b></p>	 <p>Powered by <b>Sterilight</b></p>
	<ul style="list-style-type: none"> <li>Most popular, cost effective UV disinfection system for recommended flow rates up to 6 GPM (23 lpm)</li> <li>Designed for use in a smaller home or cottage</li> </ul>	<ul style="list-style-type: none"> <li>Popular “work horse” disinfection system for recommended flow rates up to 10 gpm (38 lpm)</li> <li>Cost-effective unit is suitable for whole-home disinfection in the average residence</li> </ul>	<ul style="list-style-type: none"> <li>NSF 55 Class B Certified version of the S5Q-PA</li> <li>Suitable for smaller applications, this system is NSF (B) validated for flow rates up to 3.6 gpm (13 lpm)</li> </ul>	<ul style="list-style-type: none"> <li>NSF 55 Class B Certified version of the S8Q-PA</li> <li>Suitable for use in an average home, this system is NSF (B) validated for flow rates up to 7 gpm (26 lpm)</li> </ul>
			<b>PRICE REDUCTION</b>	<b>PRICE REDUCTION</b>
<b>PART NUMBERS</b>				
N. America (NEMA 5-15P)	<b>S5Q-PA</b>	<b>S8Q-PA</b>	<b>SV5Q-PA</b>	<b>SV8Q-PA</b>
EU CEE (CEE 7/7)	<b>S5Q-PA/2</b>	<b>S8Q-PA/2</b>	--	--
AUS/NZ (AS 3112)	<b>S5Q-PA/2A</b>	<b>S8Q-PA/2A</b>	--	--
UK (BS 1363)	<b>S5Q-PA/2B</b>	<b>S8Q-PA/2B</b>	--	--
<b>DINSINFECTON FLOW RATES</b>				
	Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)			
16 mJ/cm <sup>2</sup>	11 GPM (42 lpm) (2.5 m <sup>3</sup> /hr)	19 GPM (72 lpm) (4.3 m <sup>3</sup> /hr)	3.6 GPM (13 lpm) (0.8 m <sup>3</sup> /hr)	7.0 GPM (26 lpm) (1.6 m <sup>3</sup> /hr)
30 mJ/cm <sup>2</sup>	6 GPM (23 lpm) (1.4 m <sup>3</sup> /hr)	10 GPM (38 lpm) (2.3 m <sup>3</sup> /hr)	--	--
40 mJ/cm <sup>2</sup>	4.5 GPM (17 lpm) (1.0 m <sup>3</sup> /hr)	8 GPM (29 lpm) (1.8 m <sup>3</sup> /hr)	--	--
<b>SPECIFICATIONS</b>				
Dimensions inch (cm)	22" x 2 1/2" (56.1 cm x 6.4 cm)	35 1/2" x 2 1/2" (90.4 cm x 6.4 cm)	22" x 2 1/2" (56.1 cm x 6.4 cm)	35 1/2" x 2 1/2" (90.4 cm x 6.4 cm)
Shipping Weight lbs (kg)	8 lbs (3.6 kg)	11 lbs (5 kg)	8 lbs (3.6 kg)	11 lbs (5 kg)
Connection Size	3/4" MNPT (1/2B - BSP)	3/4" MNPT (1/2B - BSP)	3/4" MNPT	3/4" MNPT
Power Consumption	30W	46W	30W	46W
<b>REPLACEMENT PARTS</b>				
Lamp/Quartz Sleeve Kit	S463-QL	S810-QL	S463-QL	S810-QL
UV Lamp Only	S463RL	S810RL	S463RL	S810RL
Quartz Sleeve Only	QS-463	QS-810	QS-463	QS-810
Controllor	BA-ICE-S	BA-ICE-S	BA-ICE-S	BA-ICE-S
Sediment Cartridge	--	--	--	--
Carbon Cartridge	--	--	--	--

				
	Powered by <b>Sterilight</b>	Powered by <b>Sterilight</b>	Powered by <b>Sterilight</b>	Powered by <b>Sterilight</b>
	<ul style="list-style-type: none"> <li>• Suitable for applications with water flow rates up to 9 gpm (34 lpm)</li> <li>• High output lamp technology allows for a more compact footprint without compromising performance</li> </ul>	<ul style="list-style-type: none"> <li>• Powerful, compact UV disinfection system designed for the larger home or light commercial application</li> <li>• Recommended for flow rates up to 18 gpm (68 lpm) and available with UV sensor (VH410M - Home Plus section)</li> </ul>	<ul style="list-style-type: none"> <li>• Adds integral 5 micron pre-filtration module to the VH200 UV system</li> <li>• Mounted on a reversible, heavy duty, painted steel bracket for installation flexibility and convenience</li> </ul>	<ul style="list-style-type: none"> <li>• Adds integral 5 micron pre-filtration module to the VH410 UV system</li> <li>• Mounted on a reversible, heavy duty, painted steel bracket for installation flexibility and convenience</li> </ul>
<b>PART NUMBERS</b>				
N. America (NEMA 5-15P)	<b>VH200</b>	<b>VH410</b>	<b>VH200-F10</b>	<b>VH410-F20</b>
EU CEE (CEE 7/7)	<b>VH200/2</b>	<b>VH410/2</b>	<b>VH200-F10/2</b>	<b>VH410-F20/2</b>
AUS/NZ (AS 3112)	<b>VH200/2A</b>	<b>VH410/2A</b>	<b>VH200-F10/2A</b>	<b>VH410-F20/2A</b>
UK (BS 1363)	<b>VH200/2B</b>	<b>VH410/2B</b>	<b>VH200-F10/2B</b>	<b>VH410-F20/2B</b>
<b>DISINFECTION FLOW RATES</b>				
	Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)			
16 mJ/cm <sup>2</sup>	16 GPM (60 lpm) (3.6 m <sup>3</sup> /hr)	34 GPM (130 lpm) (7.8 m <sup>3</sup> /hr)	16 GPM (60 lpm) (3.6 m <sup>3</sup> /hr)	34 GPM (130 lpm) (7.8 m <sup>3</sup> /hr)
30 mJ/cm <sup>2</sup>	9 GPM (34 lpm) (2.0 m <sup>3</sup> /hr)	18 GPM (70 lpm) (4.2 m <sup>3</sup> /hr)	9 GPM (34 lpm) (2.0 m <sup>3</sup> /hr)	18 GPM (70 lpm) (4.2 m <sup>3</sup> /hr)
40 mJ/cm <sup>2</sup>	7 GPM (26 lpm) (1.6 m <sup>3</sup> /hr)	14 GPM (54 lpm) (3.3 m <sup>3</sup> /hr)	7 GPM (26 lpm) (1.6 m <sup>3</sup> /hr)	14 GPM (54 lpm) (3.3 m <sup>3</sup> /hr)
<b>SPECIFICATIONS</b>				
Dimensions inch (cm)	17 3/4" x 3 1/2" (45 cm x 8.9 cm)	23 1/2" x 3 1/2" (59.6 cm x 8.9 cm)	17" x 10 1/2" x 18" (43 cm x 26 cm x 45 cm)	17" x 10 1/2" x 28" (43 cm x 26 cm x 71 cm)
Shipping Weight lbs (kg)	12 lbs (5.4 kg)	17 lbs (7.7 kg)	26 lbs (11.8 kg)	32 lbs (14.5 kg)
Connection Size	3/4" FNPT / 1" MNPT COMBO (1/2B - BSP)	3/4" FNPT / 1" MNPT COMBO (1/2B - BSP)	3/4" FNPT INLET / 1" MNPT x 3/4" FNPT COMBO OUTLET (1/2B - BSP)	3/4" FNPT INLET / 1" MNPT x 3/4" FNPT COMBO OUTLET (1/2B - BSP)
Power Consumption	35W	60W	35W	60W
<b>REPLACEMENT PARTS</b>				
Lamp/Quartz Sleeve Kit	QL-200	QL-410	QL-200	QL-410
UV Lamp Only	S200RL-HO	S410RL-HO	S200RL-HO	S410RL-HO
Quartz Sleeve Only	QS-001	QSO-410	QS-001	QSO-410
Controller	BA-ICE-CL	BA-ICE-CL	BA-ICE-CL	BA-ICE-CL
Sediment Cartridge	--	--	CMB-510-HF	CMB-520-HF